



| Company: | | Ship To: | | |
|---|--------------------------|--|---|------------------------------------|
| Account Number: Date: | | Address: | | |
| Quote: PO Number: | | City: | State: | |
| ATP: | | Zip: | Phone: | |
| Marked For: | | Email/Fax: | | |
| Associated Quote/Order#: | | | | Effective: 1/10/2024 |
| Clik XPe- Transit Included (K0005, E1235, E1237) Clik XPe - Transit Not Included (K0005, E1235, E1237) Width Growable Frame Price does not include one time free growth kit 165 lb weight capacity Maximum Seat Width of 18" | _ \$3014 _ \$2768 | | | |
| Frame | | | | |
| Seat Width | | Transit Optio | n | |
| See reference A on page 7 8" Not available with 14"-16" Seat Depth | N/C | Transit System_ Omit | | \$246 |
| 9" | N/C | Offset Option | 1 | |
| 10" | N/C | See Chart 1 on page 7 | | |
| Not available with 16" Seat Depth. Not available with One Arm Drive. 11" 12" 13" | N/C N/C N/C | Straight Frame_ Offset Frame_ Not available wi | ith O and -1 Sling Positions. | N/C N/C |
| 14" Not available with 8" Seat Depth | N/C | Seat Option | | |
| 15" Not available with 8"-9" Seat Depth 16" Not available with 8"-10" Seat Depth | N/C N/C | Growing Seat SI Growing Solid S Omit Seat | ling_ eat Pan (E2231) | N/C \$272 N/C |
| Coot Double | | Sling Position | | |
| See reference A on page 7 | N/C | Positions extend the fro forward. See reference | ling is approximately 4" from front down tu ame in front of the sling by that amount1 D on page 7 for further detail and restrictio | pushes the seat 1" farther ons. |
| 9" 10" | N/C N/C | 2" 1" | | N/C N/C |
| 11" 12" | N/C N/C | 0"_ Not available wi | ith Offset Frame. | N/C |
| 13" 14" 15" 16" | N/C N/C N/C N/C | | ith Offset Frame. | N/C |
| | 1\/ C | Front Caster \ Certain combinations of | vv ing of Seat Depth, Center of Gravity Position ar | nd Wheel Size may require a |
| Adjustable Depth Adds the capability to grow seat in depth. For restrictions see Chart 2 on page 7. | | forward facing caster w Forward Facing | | N/C |
| No Rear Adjustment | N/C | | | 147 |
| 1" | N/C N/C | Front Frame E | | _ |
| 3" | N/C | Angle between front sec 90°_ 85°_ 80° | at tube and ground. See reference C on pag | re 7 N/C N/C |





\$215

Backrest

| Backrest | | | | | | |
|-----------------------------------|---------------------|-------|------------------|------------------|------------------|-----|
| Back Post | Height Range | | В | ack Heigh | nt | |
| | Extra Short 1,2 | 9" | 10" | 11" | 12" | |
| Height Adjustable | Short ² | 11" | 12" | 13" | 14" ¹ | |
| (Standard or 1" Inward Offset) | Medium ² | 13" | 14" | 15" | 16" | |
| | Tall ² | 15" | 16" | 17" | 18" | |
| Fixed Height (Straight or 1" | Fixed ³ | 9" 1 | 10" 1 | 11" 1 | 12" | 13" |
| Inward Offset) | Fixed • | 14" | 15" | 16" | 17" | 18" |
| Fixed Height 2" | Fixed Offset 2" | 11" 1 | 12" ¹ | 13" ¹ | 14" ¹ | |
| Offset | Fixed Offset 2 | 15" | 16" | 17" | | |

¹ Not available with Fold Down Push Handle

Back Post Option

| Sp | lecti | ักท | rea | mi | red |
|----|-------|-----|-----|----|------|
| | CCL | OH | 109 | ш | I CU |

| Straight - No Offset | N/C |
|---|-----|
| 1" Inward Offset | N/C |
| Not available with 8" Seat Widths. | |
| 2" Inward Offset | N/C |
| Not available Height Adjustable Back Post or with 8" and 9" Seat Widths. | |
| 2" Outward Offset | N/C |
| Not available with Height Adjustable Back Post, Swing Away Armrests or 8" and 9" Seat Widths | |

| Push Handles | |
|--|---------------------|
| Omit Push Handle | N/C |
| Standard Push Handle | N/C |
| Fold Down Push Handle | \$123 |
| Not available on Height Adjustable Back Posts with 9"- | 11" Back Heights or |

Bolt-On Push Handle

Handles will be 1" - 2" above back height.

Stroller Handles

| Stroller L | landles are remi | wahla and he | pight adjuctable |
|------------|------------------|--------------|------------------|

| Ergo Stroller Handle | \$190 |
|------------------------|-------|
| Single Stroller Handle | \$174 |
| Double Stroller Handle | \$338 |

Not available with 8"-10" Seat Widths

Backrest Release Cable Color

Select desired color. If no selection is made, black will be used.

| Black Backrest Cable | Red Backrest Cable | White Backrest Cable |
|----------------------|-----------------------|-----------------------|
| Blue Backrest Cable | Yellow Backrest Cable | Orange Backrest Cable |
| Green Backrest Cable | Pink Backrest Cable | N/C |

Back Upholstery Options

Available only with Height Adjustable Back Posts. If selecting both upholstery and Axiom Back, the upholstery will be installed.

| Padded Velcro Adjustable with Standard Cover | N/C |
|---|-------|
| Not available with 17" or 18" Back Heights in combination with 8" or 9" Seat Widths. | |
| Padded Velcro Adjustable with Air Mesh Breathable Cover | \$77 |
| Not available on chair widths less than 12". | |
| Tension Adjustable with Standard Cover (E2611) | \$359 |
| Not available with 8" and 9" Seat Widths or 10" Seat Width and 1" Inward Offset. | |
| Tension Adjustable with Air Mesh Breathable Cover (E2611) Not available on chair widths less than 12". | \$400 |
| Omit | N/C |

Seat Back Angle

Standard is 90° (perpendicular to floor). Minus (-°) closes back angle. Plus (+°) opens back angle.

| Standard | d 2° | 4° | 6° | 8° | 10° | |
|----------|------|-----|-----|------|-----|-----|
| -2° | -4° | -6° | -8° | -10° | | N/(|

Front Seat Height and Casters

Select Front Seat Height in row corresponding to desired Caster Size.

Front Seat Height is measured from floor to top of seat tube at front of seat sling. Adjustable up or down by 1/2". See reference E on page 7.

| Caster Size | | | | | | | Fro | nt Seat He | ight | | | | | | |
|----------------|-------|--|-------|-----|-------|-----|-------|------------|-------|-----|-------|-----|-------|-----|-------|
| 3" | 11.5" | 12" | 12.5" | 13" | 13.5" | 14" | 14.5" | 15" | 15.5" | 16" | 16.5" | 17" | 17.5" | 18" | 18.5" |
| 4" | 12.5" | 5" 13" 13.5" 14" 14.5" 15" 15.5" 16" 16.5" 17" 17.5" 18" 18.5" 19" 19.5" | | | | | | | | | | | | | |
| 5" | 13.5" | 14" | 14.5" | 15" | 15.5" | 16" | 16.5" | 17" | 17.5" | 18" | 18.5" | 19" | 19.5" | 20" | 20.5" |
| 6" | 14.5" | 15" 15.5" 16" 16.5" 17" 17.5" 18" 18.5" 19" 19.5" 20" 20.5" | | | | | | | | | | | | | |

² Each Offset Back Post is offset 1/2" creating 1" overall offset. Only available with Standard or

^{1&}quot; Inward Offset.

³ Uses 1" tubes compatible with after-market backs. Not available with back upholstery. 2" Inward or Outward Offset Back Posts are offset 1" creating 2" overall offset. 1" Offset Back Post is offset 1/2" creating 1" overall offset.





Casters Caster Size Price .75" Rollerblade N/C 75" Lighted Rollerblade \$82 N/C 1" Polv 1" Poly Aluminum \$128 Caster \$87 1" Pneumatic 1.5" Poly \$67

\$210

| Fork Options | |
|--|-------|
| Standard Fork | N/C |
| Single Sided Fork | \$174 |
| Frog Legs Suspension Fork | \$461 |
| Not included in Colored Anodizing Package. | |
| User Weight Under 80 lbs | N/C |
| User Weight 80-120 lbs | N/C |
| User Weight 120-160 lbs | N/C |
| | |

Footrest

1.5" Soft Roll Aluminum

| Footplates | |
|--|------------------|
| Aluminum Angle Adjustable (K0040) Not available with Front Seat Heights less than 14.5". | \$97 |
| Aluminum Angle Adjustable with Riser (K0040, K0037) | _\$190 |
| High Mount Aluminum Angle Adjustable (K0040, K0037) Angle Adjustable Flip Under (K0040, K0037) | _\$164 _\$190 |
| Not available with footrest widths less than 9" or with Front Seat Heights less than 15". See reference F on page 8. | |
| High Mount Angle Adjustable Flip Under (K0040, K0037) Not available with 16" Seat Width in combination with Offset Frame. | _\$318 |

Seat to Footrest Length

Measured from front edge of seat sling to top, rear of footrest. Footrest length at least 2.5" shorter than Front Seat Height

| recommended. | See reference G | on page 8. | | | |
|--------------|-----------------|------------|-----|-------|-----|
| 5.5" | 6" | 6.5" | 7" | 7.5" | 8" |
| 8.5" | 9" | 9.5" | 10" | 10.5" | 11" |
| 11.5" | 12" | 12.5" | 13" | 13.5" | 14" |
| 14.5" | 15" | 15.5" | 16" | 16.5" | 17" |
| 17.5" | 18" | | | | |

Rear Seat Height and Wheels

Rear Seat Height and Wheels

Select Rear Seat Height in row corresponding to desired Wheel Size. For proper setup, selection is required when omitting rear wheels. Measured from floor to top of seat tube at front of back post. Rear Seat Height is custom to needs. See reference H on page 7.

| Wheel Size | | | | | | | | Rear Sea | t Height | | | | | | | |
|------------|--------------------|-----|-------|-----|-------|-----|-------|----------|----------|-----|-------|-----|-------|-----|-------|-----|
| 18" | 11.5" ¹ | 12" | 12.5" | 13" | 13.5" | 14" | 14.5" | 15" | 15.5" | 16" | 16.5" | 17" | 17.5" | 18" | 18.5" | 19" |
| 20" | 12.5" ¹ | 13" | 13.5" | 14" | 14.5" | 15" | 15.5" | 16" | 16.5" | 17" | 17.5" | 18" | 18.5" | 19" | 19.5" | 20" |
| 22" | 13.5" ¹ | 14" | 14.5" | 15" | 15.5" | 16" | 16.5" | 17" | 17.5" | 18" | 18.5" | 19" | 19.5" | 20" | | |
| 24" | 14.5" ¹ | 15" | 15.5" | 16" | 16.5" | 17" | 17.5" | 18" | 18.5" | 19" | 19.5" | 20" | | | | |

1 Available only with Low Profile tires

One Arm Drive

\$1532 One Arm Drive - Quick Release (E0958) Available only with 20", 22" and 24" spoke wheels and Quick Release axles.

Spoke wheel style is exclusive to OAD. Standard handrim will be Aluminum anodized. Rear Wheel Spacing limitations exist based on camber and armrest selections. Not available on 10" wide chairs.

| Left Side Drive | N/C |
|---------------------------|-------|
| Right Side Drive | N/C |
| Aluminum Drive Handrim | N/C |
| Poly Coated Drive Handrim | \$205 |

Spinergy Options

Select spoke color and handrim tab for Spinergy wheels.

Spoke Color

N/C. Black Spokes Red Spokes White Spokes Blue Spokes

Handrim Mount

If no selection is made, standard will be used.

Close Mount

Rear Wheels

No selection needed with One Arm Drive

| | | | Rear | Wheel Siz | :e | |
|------------|--------------------------|--------|------|-----------|-----|-----|
| | | Price | 18" | 20" | 22" | 24" |
| ъ | MAXX Spoke | N/C | | | | |
| Ţ | Mag | \$56 | | | | |
| Wheel Type | Colored Mag ¹ | \$108 | | | | |
| Rear V | Spinergy Spox | \$938 | | | | |
| æ | Spinergy LX | \$1177 | | | | |

1 Mag Color Selection on page 7

N/C

Axles

No selection needed with Drum Brake.

| Quick Release | N/C |
|---------------------------|-------|
| Quad Quick Release | \$190 |
| N. 1. 11 11 11 14 C 1 L 1 | |

Not available with Mag or Spinergy wheels.

Rear Wheel Spacing

Adjustable up to .5" outward. Minimum spacing with offset frame is 1.25" with 0° camber, 1° with 2° or 4° camber and .75" with 6° or 8° camber. .75" minimum with 0° camber on standard frame. 0° Camber and Mag wheel combination requires 1" minimum Rear Wheel Spacing. No selection needed with Wheelchair Drive Ready option. .5" and .75" not available with One Arm Drive. See Reference J on page 7.

| 0.5" | 0.75" | 1" | 1.25" | 1.5" | 1.75" | | N/C |
|------|-------|----|-------|------|-------|--|-----|
|------|-------|----|-------|------|-------|--|-----|





| Full Profile | |
|---|-------|
| Street Pneumatic 1 3/8" (E2211, E2212) | N/C |
| Full Poly 1 3/8" (E2218) | \$77 |
| Pneumatic with Airless Insert 1 3/8" (E2211, E2213) | \$97 |
| Low Profile | |
| Low Poly 1" (E2218) | \$77 |
| Sentinel Solid Tire 1" (E2218) | \$108 |
| Not available on 18" wheel size or 20" and 22" Mag wheels | |
| High Pressure 1" (E2211, E2212) | \$99 |
| Not available on Mag wheel or 18" wheel size | |
| Schwalbe Marathon Plus Evolution 1" (E2211, E2212) | \$159 |
| Available only on 24" MAXX Performance or Spinergy wheels | |

Handrims

No selection needed with One Arm Drive.

Standard Handrims

| Aluminum Anodized | N/C |
|---|-------|
| Plastic Coated | \$123 |
| Projection (8 Vertical Projections) | \$359 |
| Available only with full profile tires in combination with 22", 24", and MAXX Spoke wheels, or 22" and 24" Mag wheels | d 26" |
| Omit Handrim | N/C |

Ergonomic Handrims

Not available with 20" or 26" wheels. Tab mount only available with 24" wheels.

| Lite Regular Grip | \$477 |
|-----------------------|-------|
| Standard Regular Grip | \$456 |
| Lite Extra Grip | \$528 |
| Standard Extra Grip | \$507 |
| Lite Omit Grip | \$405 |
| Standard Omit Grip | \$354 |

Handrim Option

| or relicio or ip | , | |
|------------------|--|-----|
| Not available o | on Plastic Coated or Projection Handri | ms. |

Wheelchair Drive Ready

Chair will ship from Ki Mobility with adaption kit installed for selected Alber system. Order system separately from Alber USA. Select Rear Seat Height (full profile selections only) in drive wheel size on Rear Seat Height chart above. Requires Rear Anti-Tips. Not available with 5th Wheel or Spinergy wheels.

| e-motion Ready | N/C |
|----------------|-----|
| twion Ready | N/C |

Camber Selection

| 0 Degree Camber | 3 Degree Camber | N/C |
|-----------------|-----------------|-----|
| | | |

Center of Gravity Preset

Measured from front of back post to center of rear axle. 0" indicates axle will be directly under back post. Center of Gravity setup may be limited with certain configurations. 2" minimum Center of Gravity with 5th Wheel and One Arm Drive and 0" minimum with Transit Option. See reference I on page 7.

| reference ron page 7. | | | |
|-----------------------|--------|-----|-------|
| Amputee Positions | | | |
| -1.5" | -1.25" | -1" | 75" |
| 5" | 25" | 0" | .25" |
| Standard Positions | | | |
| .5" | .75" | 1" | 1.25" |
| 1.5" | 1.75" | 2" | 2.25" |
| 2.5" | 2.75" | 3" | 3.25" |
| 3.5" | 3.75" | 4" | 4.25" |

Rear Wheel Camber

\$67

The following apply if One Arm Drive is selected: 6° and 8° not available. 4° not available with T-Arms. 0° required with the combination of a 5th Wheel and Seat Widths less than 16° .

| 1 / 11113. 0 | requi | ii ca mi | in the c | ionibiliation of a 5th Wheel and Seat What is less than 10. | |
|--------------|-------|----------|----------|---|-----|
| O° | 2° | 4° | 6° | 8° | N/C |

Wheel Locks

| Wheel Lock | |
|---|-------|
| Push to Lock | N/C |
| Push to Lock Flush Mount | N/C |
| Not available with Seat Depths less than 11" or Offset Frame. | |
| Pull to Lock | N/C |
| Low Profile Scissor Lock | \$67 |
| Not available with Low Poly, Full Poly, Sentinel tires or Offset Hanger. | |
| Drum Brake (E2228) | \$574 |
| Available only with 20", 22" and 24" MAXX Spoke wheels. Not available with Fold Down Push Handles or Ergo and Single Stroller Handles without integrated push handles. Axle is Quick Release. | |
| Dual - Drum Brake with Push to Lock (E2228) | \$677 |
| Available only with 20", 22" and 24" MAXX Spoke wheels. Not available with Fold Down Push Handles or Ergo and Single Stroller Handles without integrated push handles. Axle is Quick Release. | |
| Dual - Drum Brake with Pull to Lock (E2228) | \$677 |
| Available only with 20", 22" and 24" MAXX Spoke wheels. Not available with Fold Down Push Handles or Ergo and Single Stroller Handles without integrated push handles. Axle is Quick Release. | |
| Omit | N/C |

| Wheel Lock Options | |
|--|-------|
| Extension Handles (E0961) | \$84 |
| Grade Aids (E0974) Available only with Push to Lock Wheel Locks and Pneumatic or Pneumatic w/ Airless Insert tires. | \$154 |





Armrests

| Armrest Type | Length | | Price |
|---|--------|--|-------------|
| 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | | ¢040 |
| Height Adjustable T-Arm Tall (11.5"-15") E0973 ¹ | Full | | \$318 |
| H : H A P A D L T A 22 (0 5 H 40 5 H) 50070 1 | Desk | | #040 |
| Height Adjustable T-Arm (8.5"-13.5") E0973 ¹ | | | \$318 |
| Height Adjustable T-Arm Low (6.5"-10.5") E0973 ² | | | ¢040 |
| | | | \$318 |
| Angle Adjustable Locking Extendable Flip Up ³ | | | ¢070 |
| | | | \$272 |

- 1 Not available with Seat Depths less than 13". 16" minimum Seat Depth with Offset Frame. 1.25" minimum Rear Wheel Spacing.
- 2 Not available with Seat Depths less than 12". 14" minimum Seat Depth with Offset Frame.
- 1.25" minimum Rear Wheel Spacing. If requested configuration is unavailable, Standard Height T-Arm will be used.
- 3 Requires Fixed Height Backrest. Not available with backrest heights less than 12"
- 4 Seat Depth plus Sling Position must be at least 10". Seat Depth plus Sling Position must be at least 12" with Offset Frame 1.25" minimum Rear Wheel Spacing.
- 5 Requires Fixed Height Backrest. Not available with Arm Pads, Back Heights less than 13" or Back Heights less than 14" with Offset.

| 6 Not available with Arm Pads or Outward Offset Back Posts. If selection is not available with |
|--|
| rear wheel and rear seat height configuration, then Tall Swing Away armrest will be used. |
| 7 Not available with Arm Pads or Outward Offset Back Posts |

| Armrest Type | Price |
|--|-------|
| Height Adjustable Pediatric Desk (6.5" - 10") E0973 ⁴ | \$236 |
| Tubular Flip Up ⁵ | N/C |
| Swing Away (7"-9") E0973 ⁶ | \$244 |
| Tall Swing Away (9.25" - 11.25") E0973 ⁷ | \$244 |
| Omit Armrests | N/C |

| Arm Pads | |
|--|------|
| Standard Arm Pad | N/C |
| Waterfall Arm Pad | \$26 |
| Not available with Angle Adjustable Locking Extendable Flip Up Armrest. | |
| Foam Grip | N/C |
| Available only with Angle Adjustable Locking Extendable Flip Up Armrest. | |

Side Guards

Direct Mount Side Guards

Not available with T-Arms or Height Adjustable Pediatric Desk Armrests.

Composite Side Guards - Adult - Direct Mount Receiver (KO108) \$147 Seat Depth plus Sling Position must be at least 12".

Composite Side Guards - Pediatric - Direct Mount Receiver (K0108)___\$159 Seat Depth plus Sling Position must be at least 10".

Clamp-On Mount Side Guards

Calf Stran

10" minimum Seat Depth. Not available with T-Arms or Height Adjustable Pediatric Desk

Aluminum Adjustable Fender w/Foam Pad - Clamp-On Receiver - Black \$313 Matte (K0108) Aluminum Adjustable Fender w/Foam Pad - Clamp-On Receiver -\$364 Match Frame Color (K0108) Carbon Fiber Adjustable Fender - Clamp-On Receiver (KO108) \$528

Accessories

5th Wheel Rotating removable rear caster Standard 5th Wheel (E0971) \$256 Dynamic 5th Wheel (K0108) \$302 Soft Elastomer Firm Elastomer N/C

Both elastomers are included; the selected elastomer will be installed.

| Anti-Tip | |
|------------------------|-------|
| Rear Anti-Tips (E0971) | \$169 |
| Omit | N/C |

| Call Strap | |
|--|-------|
| Not available with 8" or 9" wide chairs. | |
| Velcro Adjustable (K0038) | \$41 |
| Padded Velcro Adjustable (K0038) | \$70 |
| Bodypoint Padded AeroMesh (K0038) | \$121 |
| | |





| Pelvic Positioning Belts | |
|--|--------------------------------|
| 1" Auto Buckle Pelvic Positioning Belt (E0978) 1" Padded Auto Buckle Pelvic Positioning Belt (E0978) 1 1/2" Auto Buckle Pelvic Positioning Belt (E0978) 1 1/2" Padded Auto Buckle Pelvic Positioning Belt (E0978) | \$82 \$174 \$82 \$174 |
| Small Bodypoint Evoflex - Pelvic Stabilizer (16-24") (E0978) Medium Bodypoint Evoflex - Pelvic Stabilizer (19-29") (E0978) Large Bodypoint Evoflex - Pelvic Stabilizer (25-37") (E0978) | \$193 \$193 \$193 |

| 1" Padded Auto Buckle Pelvic Positioning Belt (E0978) | \$174 |
|---|-------|
| 1 1/2" Auto Buckle Pelvic Positioning Belt (E0978) | \$82 |
| 1 1/2" Padded Auto Buckle Pelvic Positioning Belt (E0978) | \$174 |
| Small Bodypoint Evoflex - Pelvic Stabilizer (16-24") (E0978) | \$193 |
| Medium Bodypoint Evoflex - Pelvic Stabilizer (19-29") (E0978) | \$193 |
| Large Bodypoint Evoflex - Pelvic Stabilizer (25-37") (E0978) | \$193 |
| | |
| | |


| Spoke Guards | |
|---|----------|
| Clear Spoke Guards (K0065) Not available with Mag wheel. | \$118 |
| Black Spoke Guards (K0065) | \$118 |
| Not available with 18" or 20" wheel sizes or Mag wheel. | . |
| Blue Monster Spoke Guards (K0065) (1) | \$256 |
| Robo Fun Spoke Guards (K0065) (1) | \$256 |
| Tutu Cute Spoke Guards (K0065) (1) | \$256 |
| Tuxedo Time Spoke Guard (K0065) (1) | \$256 |
| | |

1 Available only with 20" and 22" wheel sizes. Not available with Mag wheel.

| Tool Kit | \$46 |
|---|-------|
| Removable Underseat Pouch | \$51 |
| Pediatric Ki Mobility Backpack Best fit on chairs more than 8" wide. | \$67 |
| Ki Mobility Backpack | \$67 |
| Luggage Carrier | \$87 |
| Cane and Crutch Holder | \$200 |
| Canopy with Hardware (K0108) See image to the left | \$280 |

Belt Mounting Kit

Ki Mobility Belt Mounting Clamp \$51



Color

Color

Frame Color: Select desired frame and accent colors. Accent color is used on backrest rigidizer bar and front caster wings; if no accent color is selected, frame color will be used.

| | | | Colors | | | | | | | | | | | | | | | | | | | |
|-----------|-------|-------|------------|----------------|------------|--------------|-----------|--------|--------------|-----------------|--------|------|--------|---------------|---------------|---------------------|-----------------|----------------|-----------|------------|--------------|--------------|
| Options | | Gloss | Gloss N | | | | | | | | Matte | | | | | | | | | | | |
| | Price | Black | Blue Skies | Bubblegum Pink | Candy Blue | Candy Purple | Candy Red | Copper | Granny Smith | Metallic Orange | Silver | Teal | Yellow | Charcoal Gray | Emerald Green | Iridescent Burgundy | Iridescent Navy | Military Green | Retro Red | Royal Blue | Shadow Black | Smooth White |
| Frame | N/C | | | | | | | | | | | | | | | | | | | | | |
| Accent | N/C | | | | | | | | | | | | | | | | | | | | | |
| Mag Color | | | | | | | | | | | | | | | | | | | | | | |

Color Anodized Options

Select desired color. If no selection is made, black will be used.

| | Color | Black ¹ | Blue | Bright Green | Gold | Orange | Pewter | Pink | Purple | Red |
|--------|--------------------------|--------------------|------|--------------|------|--------|--------|------|--------|------|
| | Retail | N/C | \$26 | \$26 | \$26 | \$26 | \$26 | \$26 | \$26 | \$26 |
| | Back Plates ² | | | | | | | | | |
| | Camber Tube ³ | | | | | | | | | |
| Option | Towers | | | | | | | | | |
| | Side Guard Receiver | | | | | | | | | |
| 0 | Caster Fork ³ | | | | | | | | | |
| | CG Clamp | | | | | | | | | |
| | 5th Wheel Split Clamp | | | | | | | | | |

- 1 Black is no charge
- 2 Not available with Transit Option
- 3 Available only with Standard or Single Sided





References

A. Seat Width See Diagram 1

Measured from outside of frame tube on one side to outside of frame tube on other side.

B. Seat Depth See Diagram 3

Measured from front of back posts to front edge of seat sling. Seat sling starts at beginning of bend at front of frame.

C. Front Frame Bend See Diagram 3

Angle between front seat tube and ground.

D. Sling Position See Diagram 2

With 0 Sling Position, sling is approximately 4" from the front tube. The 1" and 2" Sling Positions extend the frame in front of the sling by that amount. -1 pushes the seat 1" farther forward. See Charts 1 and 2 for more detail.

E. Front Seat Height See Diagram 1

Measured from floor to top of seat tube at front of seat sling.

F. Footrest Width See Diagram 1

Measured from inside of front tube to inside of front tube on other side. Footrest width is listed below for each seat width. See Chart 1 for more detail.

G. Seat to Footrest Length See Diagram 3

Measured from front edge of seat sling to top of rear of footrest. Footrest length of at least 2.5" shorter than front seat height recommended.

H. Rear Seat Height See Diagram 3

Measured from floor to top of seat tube at front of back post. Rear seat height is custom to needs.

I. Center of Gravity Preset See Diagram 3


Measured from front of back post to center of rear axle. 0" indicates axle will be directly under back post.


J. Rear Wheel Spacing See Diagram 1

Measured from outside of seat back to inside of rear tire. Adjustable up to .5" outward.

Chart 1

| F. Footrest Width | | | | | | | | | |
|-------------------|-------------------------------|--------------|--|--|--|--|--|--|--|
| Seat Width | Straight Frame (Diagram 1) | Offset Frame | | | | | | | |
| 8" | 5.75" | 9" | | | | | | | |
| 9" | 6.75" | 10° | | | | | | | |
| 10" | 7.75" | 11" | | | | | | | |
| 11" | 8.75" | 12" | | | | | | | |
| 12" | 9.75" | 13" | | | | | | | |
| 13" | 10.75" | 14" | | | | | | | |
| 14" | 11.75" | 15" | | | | | | | |
| 15" | 12.75" | 16" | | | | | | | |
| 16" | 13.75" | 17" | | | | | | | |








Chart 2

| Sling P | Sling Position / Adjustable Depth / Seat Depth Compatibility | | | | | | | | | | | |
|---------------|--|---------|----|----|----|----|----|----|----|----|--|--|
| | | -1", 0" | • | | 1" | | 2" | | | | | |
| Ad | Adjustable Depth | | 2" | 3" | 1" | 2" | 3" | 1" | 2" | 3" | | |
| | 14" | | | | | | | | | X | | |
| Seat Depth | 15" | | | | | | X | | X | X | | |
| | 16" | | | Х | | х | х | х | Х | х | | |

"X" indicates Sting Position, Adjustable Depth and Seat Depth combination is not available.

-1" Sting Position, 0" Adjustable Depth and 8" - 13" Seat Depths have no restrictions.